

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 170 196 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
09.01.2002 Bulletin 2002/02

(51) Int Cl.7: **B62D 6/00**
// B62D101:00, B62D117:00,
B62D153:00

(21) Application number: 01305416.8

(22) Date of filing: 22.06.2001

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

- Burton, Anthony Walter
Solihull, West Midlands B37 0DP (GB)
- Williams, Andrew James Stephen
Solihull, West Midlands B94 6LD (GB)
- Cheel, John Nicholas
Harborne, Birmingham B17 0EU (GB)
- Jones, Russell Wilson
Warwickshire CV37 9EU (GB)

(30) Priority: 29.06.2000 GB 0015832
17.04.2001 GB 0109320

(71) Applicant: **TRW LUCAS VARITY ELECTRIC
STEERING LIMITED**
Wednesbury, West Midlands WS10 7SY (GB)

(74) Representative: **Tranter, Andrew David**
Barker Brettell 138 Hagley Road Edgbaston
Birmingham B16 9PW (GB)

(72) Inventors:
• Stevens, Simon David
Billesley, Birmingham B13 0DP (GB)

(54) **Improvements relating to electrical power assisted steering systems**

(57) An electric power assisted steering system is disclosed in which a torque demand signal (8) is generated and applied to an electric motor (1) operatively connected to a steering mechanism (5) in order to assist a driver of the vehicle when steering the vehicle. The torque demand signal (8) includes a damping component that is dependent upon a measurement of torque

T carried by the steering mechanism and a measurement of the angular velocity ω of the steering mechanism. The torque produced by the motor (1) is not obtrusive during "hands-on" manoeuvres but provides enhanced damping in other manoeuvres such as a steering flick.

To be accompanied, when published, by Figure 2 of the drawings.




Fig. 2

Description

[0001] This invention relates to improvements in electrical power assisted steering systems of the kind in which an electrical motor is adapted to apply an assistance torque to a steering component such as a steering column so as to reduce the driver effort required to control the vehicle.

[0002] In a simple electric power assisted steering system a torque sensor is provided which is arranged so that the level of torque in a steering column is measured. From this measurement a controller calculates the value of a torque demand signal which is indicative of the torque that is to be generated by an electric motor attached to the steering column. The motor applies a torque to the column of the same sense as that demanded by the driver and thus reduces the effort needed to turn the wheel.

[0003] A problem with this simple arrangement occurs in certain driving manoeuvres which excite a vehicle yaw mode transient response - leading to so-called "fish-tailing" of the vehicle. These manoeuvres are typically the result of "unsupported" driver actions on the handwheel such as rotational "flicks" where the driver applies a rapid handwheel angle change but does not follow it through with any substantial applied torque or perhaps releases the handwheel after initiating a rapid turn.

[0004] In such circumstances it is desirable that the handwheel returns to the central "straight-ahead" position quickly and with a minimum amount of overshoot or oscillation. In general, however, geometric and inertial effects of the steering system contribute to a free mode yaw response that is lightly damped and quite oscillatory - particularly at high vehicle speeds.

[0005] It is known in the art to overcome this problem by including a damping component within the torque demand signal that is used to drive the motor. This damping component in some sense mimics the mechanical phenomenon of viscous friction through software by generating a component of torque demand that is a function of the handwheel velocity. The damping component may generally increase in magnitude as a function of steering angular velocity from zero torque at zero rotational speed to a maximum at some arbitrary maximum speed. In effect, the damping component reduces the actual torque output by the motor, and hence the amount of assistance, in a particular instance when the velocities are high.

[0006] In accordance with a first aspect the invention provides an electric power assisted steering system comprising a steering mechanism which operatively connects a steering wheel to the roadwheels of the vehicle, a torque sensing means adapted to produce a first output signal indicative of the torque carried by a portion of the steering mechanism, a means for producing a second output signal indicative of the angular velocity of a portion of the steering mechanism, an electric motor

operatively connected to the steering mechanism, a signal processing unit adapted to receive the two signals and to produce a torque demand signal representative of a torque to be applied to the steering mechanism by the motor, and a motor drive stage adapted to provide a drive current to the motor responsive to the torque demand signal, and in which the torque demand signal includes a damping component that is dependent upon both the first output signal and the second output signal.

[0007] By making the damping component a function of torque as well as angular velocity of a portion of the steering mechanism, it has been found that the damping component does not become intrusive during "hands-on" slalom manoeuvres yet the damping remains effective in improving yaw response in other circumstances such as a steering flick.

[0008] The magnitude of the damping component preferably generally increases over a range of steering velocity values bounded by a first velocity and a second, higher, velocity. Thus, as the steering mechanism angular velocity is increased more damping is introduced. The portion of the steering mechanism may comprise a steering column and the first velocity may correspond to zero column velocity. The second velocity may correspond to the maximum expected column velocity or some other arbitrarily selected value. Alternatively, a deadband may be provided whereby the damping component value remains at or about zero over a range of velocities bounding zero velocity. The width of this deadband may be varied in use, and may for example be varied as a function of vehicle speed or another measured parameter.

[0009] The magnitude of the damping component may generally increase linearly as a function of column velocity over the whole or a part of the range of values. Thus, the value of the damping component may become generally higher as the angular velocity of the steering wheel increases. However, a non-linear relationship may exist between velocity of the steering wheel and the damping component value.

[0010] In the preferred arrangement the rate of increase of the magnitude of the damping component between the first and second values preferably decreases as a function of applied torque. The damping component, in one arrangement, may be produced by generating a scaling value that is a function of torque, generating an intermediate damping value that is a function of column velocity, and multiplying the two values together to produce the damping component.

[0011] The scaling value may vary from a maximum value at zero applied torque to a minimum value at a predetermined maximum applied torque. In this case, for torque values at or above the maximum then a zero valued damping component will be produced.

[0012] The scaling value may be adapted to be substantially zero valued over a range of measured torque values bounding zero torque. This provides a deadband either side of zero torque about which for a given steer-

ing wheel velocity a maximum damping component is produced, improving steering feel for high speed on centre manoeuvres.

[0013] In a further refinement the width of the dead-band may be varied as a function of the speed of the vehicle to which the steering system is fitted. A measurement of vehicle speed may therefore be provided to a third input of the signal processor.

[0014] The torque demand signal may include an assistance torque signal that is a function of torque in the steering mechanism. The assistance torque signal may generally increase with increasing torque applied by the driver. The signal processor may be adapted to produce the torque demand signal by combining the damping component with the assistance torque signal. Preferably the damping component is subtracted from the assistance torque signal.

[0015] The assistance torque signal may be a function of other variables such as vehicle speed.

[0016] The signal processor may calculate the value of the damping component for any given combination of torque and steering wheel velocity from entries in a look-up table. In this case, each or specific combinations of steering velocity and driver input torque will access a specified value stored in the table.

[0017] In a preferred alternative, the value of the damping component may be derived by entering the velocity, torque and optionally vehicle speed values into a suitable equation.

[0018] Whilst the provision of a damping component that is a function of torque as well as angular velocity of the steering column provides appropriate levels of damping during "hands-on" slalom manoeuvres it can, in certain circumstances, induce unwanted torque variations in the steering column shaft. For example, when a high frequency driver applied torque is generated, or the column kicks back due to impacts on the road wheels, the torque dependent damping component can interact with the applied torque setting up an unpleasant oscillation. Thus, the driver applied torque can affect the damping torque which in turn affects the driver applied torque and so on.

[0019] In a refinement, to ameliorate such an effect the damping component may be filtered to remove high frequency variations in the damping component caused by high frequency changes in the column torque. Thus, the system may include limiting means adapted to limit the rate of change of the damping component due to corresponding changes in column torque to a predetermined maximum rate.

[0020] Preferably, the rate limiting means may comprise a filter. This may comprise a lower pass filter, when in one arrangement may have a cut-off frequency of approximately 3Hz (Hertz).

[0021] In a most convenient arrangement, where the damping component comprises the product of a scaling value that is a function of torque and an intermediate damping value that is a function of the column velocity,

the limiting means may be arranged to limit the rate of change of the scaling value over time. The scaling value may be low-pass filtered prior to multiplication by the intermediate damping value to generate the damping component.

[0022] The low-pass filter may be a frequency domain filter but may be of any known kind, typically a discrete digital filter implemented on a microprocessor. Of course, any processing of the scaling value which limits the maximum rate of change of the scaling value over time could be employed.

[0023] There will now be described, by way of example only, one embodiment of the present invention with reference to the accompanying drawings of which:

Figure 1 is a schematic diagram of an electric power assisted steering system in accordance with the present invention;

Figure 2 is a block diagram illustrating the functional steps undertaken within the signal processing unit of the system of Figure 1;

Figure 3 illustrates the relationship between the torque applied by the driver and the assistance torque value generated;

Figure 4 illustrates the relationship between the damping component and the column velocity;

Figure 5 illustrates the relationship between the value of the damping component and driver applied torque; and

Figure 6 is a block diagram illustrating an alternative set of functional steps undertaken with the signal processing unit of the system of Figure 1.

[0024] An electric power assisted steering system is illustrated in Figure 1 of the accompanying drawings. The system comprises an electric motor 1 which acts upon a drive shaft 2 through an (optional) gearbox 3. The drive shaft 2 terminates with a worm gear 4 that cooperates with a wheel provided on a portion of a steering column 5 or a shaft operatively connected to the steering column.

[0025] The steering column 5 carries a torque sensor 6 that is adapted to measure the torque carried by the steering column that is produced by the driver of the vehicle as the steering wheel (not shown) and hence steering column is turned against the resisting force provided by the vehicles road wheels (also not shown). The output signal T from the torque sensor 6 is fed to a first input of a signal processing unit 7.

[0026] An angular velocity sensor is also provided on the steering column shaft. As shown in Figure 1 this is an integral part of the torque sensor 6. This produces an output signal indicative of the angular velocity ω of

the shaft. The output from the velocity sensor is fed to a second input of the signal processing unit 7. This may comprise a electronic processor unit or other electronic circuitry.

[0027] The signal processing unit 7 acts upon the two input signals to produce, as its output, a torque demand signal 8 that is passed to a motor controller 9. The motor controller 9 converts the torque demand signal 8 into drive currents for the electric motor 1.

[0028] The value of the torque demand signal 8 corresponds to the amount of assistance torque to be applied to the steering column by the electric motor 1. The value will vary from a minimum value corresponding to maximum output torque for the motor in one sense, through zero torque when the demand signal is zero, to a maximum motor torque of the opposite sense.

[0029] The motor controller 9 receives as its input the torque demand signal and produces currents that are fed to the motor to reproduce the desired torque at the motor drive shaft 2. It is this assistance torque applied to the steering column shaft 5 that reduces the effort needed by the driver to turn the wheel.

[0030] Figure 2 illustrates the functional steps undertaken by the signal processing unit 7 in producing the torque demand signal 8. It can be seen that the torque demand signal 8 is produced as two components: an assistance torque signal 10 and a damping component 11. These two components 10, 11 are combined within the signal processor to form the final torque demand signal 8.

[0031] The assistance torque signal 10 is derived as a function of the torque in the steering column as measured by the torque sensor 6. The relationship between the measured torque and the assistance signal is essentially linear as shown in the plot of Figure 3. However, other possible relationships may be used to map the torque to the assistance signal. In both cases, as torque increases the magnitude of the assistance signal increases. It will also be understood that the assistance torque signal 10 may be dependent upon other parameters such as vehicle speed if required. In that case it is typical to reduce the value of the assistance torque signal 10 at high speeds to enhance stability and increase it at very low speeds to ease parking manoeuvres.

[0032] The damping component is produced as a function of both the measured torque and column velocity. As shown in figure 4, an intermediate damping signal 12 is produced as a linear function of column velocity. The intermediate damping signal 12 increases in value from zero at zero column velocity to a maximum value at a predetermined column velocity (typically 2 revolutions per second). Of course, for different applications both the peak damping value and the velocity corresponding to this value may be varied. Above 2 revolutions per second the intermediate damping signal value remains constant. A deadband is also provided around zero velocity which may be of variable width. Thus, the value of the damping component remains at or about

zero for a range of velocities within the deadband.

[0033] The intermediate damping signal 12 is then modified as a function of torque by calculating a scaling value 13. As shown in Figure 5 of the accompanying drawings, the scaling value 13 is a fractional value that is a function of torque carried by the steering column. The scaling value increases from unity at zero applied torque to zero at a predetermined threshold applied torque. A deadband is also provided whereby the scaling value remains at or around unity for small torque values around zero torque. The width of the deadband is preferably chosen to exceed the maximum torque that can arise due to inertia in the system.

[0034] The intermediate signal 12 is next multiplied by the scaling factor signal 13 in order to produce the damping component 11. Finally, the signal processor subtracts the damping component 11 from the assistance torque signal 10 to produce the torque demand signal 8 used to drive the electric motor 1.

[0035] A refinement is illustrated in the block diagram of Figure 6. In this arrangement, three input values are passed to the signal processor: column velocity ω , column angular position N_{col} and column torque T .

[0036] As in the arrangement of Figure 2, the measured torque is used to produce an assistance torque signal 10 in the manner illustrated in Figure 3 of the accompanying drawings.

[0037] The damping component is also produced as a function of both the measured torque and the column velocity. However, in this arrangement two main differences can be noted as follows:

(a) The torque value T is processed to produce a scaling value 13 as for the first embodiment but this is subsequently passed through a low-pass filter 14 to remove any high-frequency torque dependent variations in value prior to combining with the intermediate signal 12 to produce the damping component; and

(b) The intermediate signal 12 is produced as a function of both column velocity ω and column absolute angle position N_{col} to introduce a position dependent deadband 15 about the straight ahead position of the steering column.

[0038] The low-pass filter 14, which is this embodiment has a cut-off frequency of 3Hz, removes the effect of high speed variation in driver applied torque combining with subsequent high frequency variations in damping component. In certain circumstances, without the presence of the low-pass filter, unwanted vibrations may be produced in the steering column.

[0039] The filter may be implemented in a variety of ways which will be readily appreciated by the person skilled in the art. A suitable frequency domain filter may be of the form:

$$X = \frac{\text{damp - first - numerator (Z)}}{\text{damp - first - denominator (Z)}}$$

where X is the filtered scaling value.

Claims

1. An electric power assisted steering assembly comprising a steering mechanism 5 which operatively connects a steering wheel to the roadwheels of a vehicle, a torque sensing means 6 adapted to produce a first output signal indicative of the torque T carried by a portion of the steering mechanism 5, a means for producing a second output signal indicative of the angular velocity of the portion of the steering mechanism, an electric motor 1 operatively connected to the steering mechanism 5, a signal processing unit 7 adapted to receive the two signals and to produce a torque demand signal 8 representative of a torque to be applied to the steering mechanism 5 by the motor 1, and a motor drive stage adapted to provide a drive current to the motor 1 responsive to the torque demand signal 8, and **characterised in that** the torque demand signal 8 includes a damping component 11 that is dependent upon both the first output signal and the second output signal.
2. An electric power assisted steering assembly according to claim 1, in which the portion of the steering mechanism comprises a steering column and the magnitude of the damping component 11 generally increases over a range of steering column velocity values bounded by a first velocity and a second, higher, velocity.
3. An electric power assisted steering assembly according to claim 2, in which the first velocity corresponds to zero column velocity.
4. An electric power assisted steering assembly according to claim 2, in which a deadband is provided whereby the damping component value remains at or about zero over a range of velocities bounding zero velocity.
5. An electric power assisted steering assembly according to claim 4, in which the width of the deadband is varied in use as a function of vehicle speed.
6. An electric power assisted steering assembly according to any one of claims 2 to 4, in which the magnitude of the damping component 11 generally increases linearly as a function of column velocity over the whole or a part of the range of values.
7. An electric power assisted steering assembly according to any one of claims 2 to 6, in which the rate of increase of the magnitude of the damping component between the first and second values decreases as a function of applied torque.
8. An electric power assisted steering assembly according to any preceding claim, in which the damping component is produced by generating a scaling value 13 that is a function of torque, generating an intermediate damping value 12 that is a function of column velocity, and multiplying the two values together to produce the damping component 11.
9. An electric power assisted steering assembly according to claim 8, in which the scaling value varies from a maximum value at zero applied torque to a minimum value at a predetermined maximum applied torque.
10. An electric power assisted steering assembly according to claim 8 or claim 9, in which the scaling value 13 is substantially zero valued over a range of measured torque values bounding zero torque.
11. An electric power assisted steering assembly according to any preceding claim, in which the torque demand signal 8 includes an assistance torque signal 10 that is a function of torque in the steering mechanism.
12. An electric power assisted steering assembly according to claim 11, in which the signal processing unit 7 is adapted to produce the torque demand signal by combining the damping component 11 with the assistance torque signal 10.
13. An electric power assisted steering assembly according to any preceding claim, in which the damping component is filtered to remove high frequency variations in the damping component caused by high frequency changes in the column torque.
14. An electric power assisted steering assembly according to claim 13, in which a limiting means 14 is provided that is adapted to limit the rate of change of the damping component due to corresponding changes in column torque to a predetermined maximum rate.
15. An electric power assisted steering assembly according to claim 14, in which the rate limited means comprises a lower pass filter 14.
16. An electric power assisted steering assembly according to any one of claims 13 to 15 when dependent from claim 6, in which the limiting means is arranged to limit the rate of change of the scaling value over time.

17. An electric power assisted steering assembly according to claim 16, in which the scaling value is low-pass filtered prior to multiplication by the intermediate damping value to generate the damping component.

5

10

15

20

25

30



35



40

45

50

55










Fig. 2

Fig. 6





Europäisches Patentamt
European Patent Office
Office pour l'émission des brevets



(11) **EP 1 170 196 A3**

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
22.01.2003 Bulletin 2003/04

(51) Int Cl.7: **B62D 5/04**
// B62D101:00, B62D117:00,
B62D153:00

(43) Date of publication A2:
09.01.2002 Bulletin 2002/02

(21) Application number: **01305416.8**

(22) Date of filing: **22.06.2001**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

- **Burton, Anthony Walter**
Solihull, West Midlands B37 0DP (GB)
- **Williams, Andrew James Stephen**
Solihull, West Midlands B94 6LD (GB)
- **Cheel, John Nicholas**
Harbone, Birmingham B17 0EU (GB)
- **Jones, Russell Wilson**
Warwickshire CV37 9EU (GB)

(30) Priority: **29.06.2000 GB 0015832**
17.04.2001 GB 0109320

(71) Applicant: **TRW LUCAS VARITY ELECTRIC**
STEERING LIMITED
Wednesbury, West Midlands WS10 7SY (GB)

(74) Representative: **Tranter, Andrew David**
Barker Brettell
138 Hagley Road
Edgbaston
Birmingham B16 9PW (GB)

(72) Inventors:
• **Stevens, Simon David**
Billesley, Birmingham B13 0DP (GB)

(54) Improvements relating to electrical power assisted steering systems

(57) An electric power assisted steering system is disclosed in which a torque demand signal (8) is generated and applied to an electric motor (1) operatively connected to a steering mechanism (5) in order to assist a driver of the vehicle when steering the vehicle. The torque demand signal (8) includes a damping component that is dependent upon a measurement of torque

T carried by the steering mechanism and a measurement of the angular velocity ω of the steering mechanism. The torque produced by the motor (1) is not obtrusive during "hands-on" manoeuvres but provides enhanced damping in other manoeuvres such as a steering flick.

To be accompanied, when published, by Figure 2 of the drawings.




Fig. 2



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 5416

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X A	EP 0 416 263 A (BOSCH GMBH ROBERT) 13 March 1991 (1991-03-13) * abstract; claims 1-4,6; figure 1 * * column 1, line 23 - column 1, line 46 * * column 2, line 2 - column 5, line 27 * -----	1-6,13 8,9,14, 15	B62D5/04 //B62D101:00, B62D117:00, B62D153:00
X A	EP 0 810 143 A (TRW INC) 3 December 1997 (1997-12-03) * abstract; figures 1,2 * * page 2, line 51 - page 3, line 23 * * page 4, line 16 - page 5, line 3 * * page 5, line 18 - page 6, line 18 * * page 6, line 46 - page 7, line 15 * * page 8, line 37 - page 8, line 47 * -----	1,2,6, 11,12 8	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			B62D
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 4 December 2002	Examiner Balázs, M
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document		T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document	

EPIC FORM 1503 03 02 (P) 01

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 5416

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

04-12-2002

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0416263 A	13-03-1991	DE 3929177 A1	07-03-1991
		DE 59002908 D1	04-11-1993
		EP 0416263 A1	13-03-1991
		JP 3092475 A	17-04-1991
EP 0810143 A	03-12-1997	US 5743351 A	28-04-1998
		BR 9703328 A	19-12-2000
		EP 0810143 A2	03-12-1997
		JP 2802267 B2	24-09-1998
		JP 10053147 A	24-02-1998

EPO FORM P4452

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

